

## TECHNICKÁ SPECIFIKACE OMSG LAUNCO 250 NS8

Lauco	60 FAC	100 N	150 NP 1500 NS	150 H 1500 HNS	200 N 200 NS 6 2000 NS	250 NS 250 NS 8 2500 NS 8	300 N 3000 NS 8
Component width (mm) B	600	1000	1500	1500	2000	2500	3000
Component height (mm) H	300	400	500	1000	500	500	500
Max. roller load (kg)	100	800	800 1000	800 1200	1000 1000 1200	1000 1000 1000	1000 2000
Blast wheels + power (kW)	4 x 4	4 x 7,5	4 x 11,0 4 x 18,5	4 x 11,0 4 x 18,5	4 x 11,0 6 x 11,0 4 x 22,0	6 x 11,0 6 x 11,0 6 x 22,0	8 x 11,0 8 x 22,0
Floor height roller conveyor (mm)	1050	1000	1200	1200 800	850 850 975	700 700 710	800 850
Width (mm) A	1450	2400	2900 3500	2900 3500	3300 4200	4500 5200	5600 6670
Length (mm) L	2500	4500	4600 6000	4600 6000	4900 6000	5900 7850	6100 7750
Height (mm) M	4280	4500	4900 6000	5800 6500	5950 6000	5550 5490 5700	5550 6300
Req. air flow (m3/h)	integrated	5000	7500 15000	7500 15000	10000 10000 20000	15000 25000 25000	20000 25000
Foundation/pit	no	no	no/yes	no/yes	yes	yes	yes

